


Kiesel
klebt am Bau®

Date of issue: 02/24/2026

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/24/2026

1 Identification

- Product identifier
- Trade name: Servoflex Trio schnell SuperTec grau
- Other means of identification
- Application of the substance / the mixture Tile adhesive
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Kiesel Bauchemie GmbH & Co. KG
Wolf-Hirth-Str. 2
D-73730 Esslingen
Germany
E-Mail:
info.canada@kiesel.com
info.usa@kiesel.com
- Information department: Laboratory, departments of enviromental protection and labor protection
- Emergency telephone number: ChemTel Expert Assiatance Hotline 800-255-2824

2 Hazard(s) identification

- Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 1A

H350 May cause cancer.



GHS05 Corrosion

Eye damage 1

H318 Causes serious eye damage.



GHS07

Skin irritation 2

H315 Causes skin irritation.

Specific target organ toxicity (single exposure) H335 May cause respiratory irritation.
3

- Label elements

- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS05 GHS07 GHS08

- Signal word

Danger

- Hazard-determining components of labeling:

Portland Cement

Quarz (SiO₂)

- Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause cancer.

May cause respiratory irritation.

- Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 1)

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Information pertaining to particular dangers for man and environment:

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3

Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *3

Fire = 0

Reactivity = 0

· Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

· Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· Composition/Information on ingredients

· Chemical characterization: Mixtures

· Description: **Mixture of the substances listed below with nonhazardous additions.**

· Dangerous components:

CAS: 14808-60-7 Quarz (SiO₂)

Carcinogenicity 1A, H350

CAS: 65997-15-1 Portland Cement

Eye damage 1, H318

Skin irritation 2, H315; Specific target organ toxicity (single exposure) 3, H335

CAS: 65997-16-2 Calcium Aluminate Cement

Skin irritation 2, H315; Eye irritation 2A, H319

CAS: 10034-76-1 Calciumsulfat-Halbhydrat

CAS: 471-34-1 Calciumcarbonat

· Additional information: **For the wording of the listed hazard phrases refer to section 16.**

4 First-aid measures

· Description of first aid measures

· General information: **Immediately remove any clothing soiled by the product. If you feel unwell, seek medical advice.**

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 2)

- **After inhalation:** *Inhalation of dusts causes irritation and swelling of respiratory organs.
In case of unconsciousness place patient stably in side position for transportation.
Seek medical treatment in case of complaints.*
- **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*
- **After eye contact:** *Rinse opened eye for several minutes under running water.
Then consult a doctor.*
- **After swallowing:** *rinse out mouth
Make patient vomit by him/herself.
The decision whether to provoke vomiting or not is to be taken by a physician.*
- **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
- **Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** *The product itself does not burn.
CO₂, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.
Use fire fighting measures that suit the environment.*
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **Special hazards arising from the substance or mixture** *Formation of toxic gases is possible during heating or in case of fire.*
- **Advice for firefighters**
- **Protective equipment:** *Wear non-circulation breathing equipment and chemical-protective clothing. Do not inhale explosion gases or fire fumes.*

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** *Avoid formation of dust.
Wear protective clothing.
Respirator must be worn if exposed to dust.
Ensure adequate ventilation
Mount respiratory protective device.*
- **Environmental precautions:** *No special measures required.*
- **Methods and material for containment and cleaning up:** *Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Pick up mechanically.*
- **Protective Action Criteria for Chemicals**

· PAC-1:

CAS: 65997-17-3 Kalk-Natron-Silikatglas

15 mg/m³

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 3)

CAS: 471-34-1	Calciumcarbonat	45 mg/m ³
CAS: 497-19-8	Soda leicht, Natriumcarbonat	7.6 mg/m ³
CAS: 6381-59-5	Kalium-Natrium-Tartrat	12 mg/m ³

· PAC-2:

CAS: 65997-17-3	Kalk-Natron-Silikatglas	170 mg/m ³
CAS: 471-34-1	Calciumcarbonat	210 mg/m ³
CAS: 497-19-8	Soda leicht, Natriumcarbonat	83 mg/m ³
CAS: 6381-59-5	Kalium-Natrium-Tartrat	130 mg/m ³

· PAC-3:

CAS: 65997-17-3	Kalk-Natron-Silikatglas	990 mg/m ³
CAS: 471-34-1	Calciumcarbonat	1300 mg/m ³
CAS: 497-19-8	Soda leicht, Natriumcarbonat	500 mg/m ³
CAS: 6381-59-5	Kalium-Natrium-Tartrat	790 mg/m ³

- Reference to other sections See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- Precautions for safe handling Keep the product out of the reach of children.
Thorough dedusting.
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with skin and eyes.
Do not breathe dust.
Breathing apparatus only if aerosol or dust is formed.
protected above to humidity
- Information about protection against explosions and fires: Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: protected above to humidity in closing rooms
- Information about storage in one common storage facility: Not required
- Further information about storage conditions: Keep away from food and drink.
Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Control parameters
- Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 4)

CAS: 14808-60-7 Quarz (SiO₂)

- PEL** Long-term value: 0.05* mg/m³
*resp. dust; 30mg/m³/‰SiO₂+2
- REL** Long-term value: 0.05* mg/m³
*respirable dust; See Pocket Guide App. A
- TLV** Long-term value: 0.025* mg/m³
*respirable particulate matter, A2

CAS: 65997-15-1 Portland Cement

- PEL** Long-term value: 50 mppcf or 15* 5** mg/m³
*total dust **respirable fraction
- REL** Long-term value: 10* 5** mg/m³
*total dust **respirable fraction
- TLV** Long-term value: 1* mg/m³
E; *as respirable fraction, A4

CAS: 10034-76-1 Calciumsulfat-Halbhydrat

- TLV** Long-term value: 10* mg/m³
*as inhalable fraction

CAS: 471-34-1 Calciumcarbonat

- PEL** Long-term value: 15* 5** mg/m³
*total dust **respirable fraction
- REL** Long-term value: 10* 5** mg/m³
*total dust **respirable fraction
- TLV** TLV withdrawn

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Do not eat or drink while working.
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the skin.
 - Avoid contact with the eyes and skin.
- **Breathing equipment:** Suitable respiratory protection for low concentrations or short-term exposure: particle filter EN 143 type P2 (medium retention capacity (solid and liquid pollutant particles))
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Breathing apparatus only if aerosol or dust is formed.
- **Protection of hands:** Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves** Rubber gloves
Nitrile rubber, NBR
- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Tightly sealed goggles.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

• **Body protection:** Long-sleeved work clothes.

(Contd. of page 5)

9 Physical and chemical properties

• Information on basic physical and chemical properties	
• Physical state	Solid
• Color:	According to product specification
• Odor:	Characteristic
• Odor threshold:	Not determined
• Melting point/Melting range:	undetermined
• Boiling point/Boiling range:	nicht anwendbar
• Flammability:	Not determined
• Explosion limits:	
• Lower:	Not determined
• Upper:	Not determined
• Flash point:	Not applicable
• Decomposition temperature:	Not determined
• pH-value at 20 °C (68 °F):	12 (5%)
• Viscosity:	
• Kinematic:	Not applicable
• Dynamic:	Not applicable
• Solubility in / Miscibility with	
• Water:	is setting hydraulically
• Partition coefficient (n-octanol/water):	Not determined
• Vapor pressure:	Not applicable
• Vapor pressure:	
• Density at 20 °C (68 °F):	1.6 g/cm ³ (13.352 lbs/gal)
• Relative density	Not determined
• Vapor density	Not applicable
• Particle characteristics	Not determined
• Other information The physical data are average values.	
• Appearance:	
• Form:	Powder
• AUTO IGNITION:	Not self igniting
• Danger of explosion:	Product does not present an explosion hazard.
• Solvent content:	
• VOC-Content	0.00 %
• Solids content:	100.0 %
• Change in condition	
• Evaporation rate	Not applicable.

10 Stability and reactivity

• Reactivity	No further relevant information available.
• Chemical stability	
• Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications. entrance of moisture
• Possibility of hazardous reactions	No dangerous reactions known.
• Conditions to avoid	No further relevant information available.
• Incompatible materials:	No decomposition if stored and applied as directed.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 6)

- **Hazardous decomposition products:** none under normal use

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:

CAS: 10034-76-1 Calciumsulfat-Halbhydrat

Oral LD50 >2,000 mg/kg (Rat)

CAS: 471-34-1 Calciumcarbonat

Oral LD50 >5,000 mg/kg (Rat)

- Primary irritant effect:

- on the skin:

Irritant to skin and mucous membranes.

- on the eye:

Strong irritant with the danger of severe eye injury.

- Sensitization:

No sensitizing effects known.

- Experience with humans:

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

The product contains cement. In combination with humidity the product provokes an alkaline reaction.

May cause eye/skin irritation.

- Additional toxicological information:

According to concentration, aqueous solution causes irritations or burns of eyes, skin and mucous membranes.

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- Interactive effects

No interactive effects between components are known.

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological information

- Toxicity

- Aquatic toxicity:

No further relevant information available.

- Persistence and degradability

No further relevant information available.

- Bioaccumulative potential

No further relevant information available.

- Mobility in soil

No further relevant information available.

- Results of PBT and vPvB assessment

- PBT:

Not applicable

- vPvB:

Not applicable

- Other adverse effects

- Ecotoxicological effects:

only by unintentional binding with much material and water is a highly pH-value possible

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 7)

· **Additional ecological information:**

· **General notes:**

Ecological injuries are not known or expected under normal use.

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Disposal in accordance with official regulations

· **Uncleaned packagings:**

· **Recommendation:**

Disposal must be made according to official regulations.

· **Recommended cleansing agent:**

Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, ADR, ADN, IMDG, IATA**

Void

· **UN proper shipping name**

· **DOT, ADR, ADN, IMDG, IATA**

Void

· **Transport hazard class(es)**

· **DOT, ADR, ADN, IMDG, IATA**

· **Class**

Void

· **Packing group**

· **DOT, ADR, IMDG, IATA**

Void

· **Environmental hazards:**

· **Marine pollutant:**

No

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable

· **Transport/Additional information:**

Not dangerous according to the above specifications.

· **Special precautions for user**

Not applicable

· **UN "Model Regulation":**

Void

US

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 8)

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture

• Sara

• Section 355 (extremely hazardous substances):

None of the ingredient is listed.

• Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

CAS: 65997-15-1	Portland Cement	ACTIVE
-----------------	-----------------	--------

CAS: 65997-16-2	Calcium Aluminate Cement	ACTIVE
-----------------	--------------------------	--------

CAS: 65997-17-3	Kalk-Natron-Silikatglas	ACTIVE
-----------------	-------------------------	--------

CAS: 471-34-1	Calciumcarbonat	ACTIVE
---------------	-----------------	--------

CAS: 497-19-8	Soda leicht, Natriumcarbonat	ACTIVE
---------------	------------------------------	--------

• Hazardous Air Pollutants

None of the ingredients is listed.

• Proposition 65

• Chemicals known to cause cancer:

CAS: 14808-60-7	Quarz (SiO ₂)
-----------------	---------------------------

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

• New Jersey Right-to-Know List:

CAS: 65997-15-1	Portland Cement
-----------------	-----------------

CAS: 9004-34-6	Cellulose
----------------	-----------

• New Jersey Special Hazardous Substance List:

None of the ingredients is listed.

• Pennsylvania Right-to-Know List:

CAS: 65997-15-1	Portland Cement
-----------------	-----------------

CAS: 9004-34-6	Cellulose
----------------	-----------

• Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

• Cancerogenity categories

• EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

None of the ingredients is listed.

• MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 9)

· Hazard pictograms



GHS05 GHS07 GHS08

· Signal word

Danger

· Hazard-determining components of labeling:

Portland Cement
Quarz (SiO₂)

· Hazard statements

Causes skin irritation.
Causes serious eye damage.
May cause cancer.

· Precautionary statements

May cause respiratory irritation.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
Employment restrictions concerning young persons must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· Other regulations, limitations and prohibitive regulations

Classified according to GEV test method as very low emission with EMICODE EC 1

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his evaluation of the product's hazards, and safety precautions to be taken in its use. The data on this SDS relate only to the specific material designated herein. We do not assume any liability for the use, or reliance in this information, nor do we guarantee its accuracy or completeness.

· Department issuing SDS: Health protection and safety

· Date of previous version 09/14/2023

· Version number of previous version: 25

· Date of preparation 02/24/2026

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoflex Trio schnell SuperTec grau

(Contd. of page 10)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin irritation 2: Skin corrosion/irritation – Category 2

Eye damage 1: Serious eye damage/eye irritation – Category 1

Eye irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 1A: Carcinogenicity – Category 1A

Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.

US