


Kiesel
 klebt am Bau®

Date of Issue: 02/24/2026

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/24/2026

1 Identification

- Product identifier
- Trade name: **Servoplan Ki 1**
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier: **Kiesel Bauchemie GmbH & Co. KG**
Wolf-Hirth-Str. 2
D-73730 Esslingen
Germany
E-Mail:
info.canada@kiesel.com
info.usa@kiesel.com
- Information department: **Laboratory, departments of environmental protection and labor protection**
- Emergency telephone number: **ChemTel Expert Assistance Hotline 800-255-2824**

2 Hazard(s) identification

- Classification of the substance or mixture


GHS08 Health hazard
Carcinogenicity 1A H350 May cause cancer.

GHS05 Corrosion
Eye damage 1 H318 Causes serious eye damage.

GHS07
Skin irritation 2 H315 Causes skin irritation.

- Label elements

- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms


GHS05 GHS08

- Signal word

Danger

- Hazard-determining components of labeling:

Quarz (SiO₂)
Portland Cement

- Hazard statements

Causes skin irritation.
Causes serious eye damage.
May cause cancer.

- Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
IF exposed or concerned: Get medical advice/attention.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 1)

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Information pertaining to particular dangers for man and environment:

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3

Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *3

Fire = 0

Reactivity = 0

· Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

· Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· Composition/Information on ingredients

· Chemical characterization: Mixtures

· Dangerous components:

CAS: 14808-60-7	Quarz (SiO ₂)
	Carcinogenicity 1A, H350
CAS: 471-34-1	Calciumcarbonat
CAS: 65997-16-2	Calcium Aluminate Cement
	Skin irritation 2, H315; Eye irritation 2A, H319
CAS: 65997-15-1	Portland Cement
	Eye damage 1, H318
	Skin irritation 2, H315; Specific target organ toxicity (single exposure) 3, H335
CAS: 10034-76-1	Calciumsulfat-Halbhydrat

· Additional information:

See also information on "8 Exposure controls and personal protective equipment".

For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

If you feel unwell, seek medical advice.

· After inhalation:

Do not breathe dust.

Inhalation of dusts causes irritation and swelling of respiratory organs.

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment in case of complaints.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 2)

- After skin contact: **Immediately wash with water and soap and rinse thoroughly.**
- After eye contact: **Rinse opened eye for several minutes under running water. Then consult a doctor.**
- After swallowing: **rinse out mouth**
The decision whether to provoke vomiting or not is to be taken by a physician.
- Most important symptoms and effects, both acute and delayed **No further relevant information available.**
- Indication of any immediate medical attention and special treatment needed **No further relevant information available.**

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: **The product itself does not burn.**
CO₂, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.
Use fire fighting measures that suit the environment.
- For safety reasons unsuitable extinguishing agents: **Water with full jet**
- Special hazards arising from the substance or mixture **Formation of toxic gases is possible during heating or in case of fire.**
- Advice for firefighters
- Protective equipment: **Wear non-circulation breathing equipment and chemical-protective clothing. Do not inhale explosion gases or fire fumes.**

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures **Ensure adequate ventilation**
Avoid formation of dust.
Respirator must be worn if exposed to dust.
- Environmental precautions: **No special measures required.**
- Methods and material for containment and cleaning up: **Use neutralizing agent.**
Dispose contaminated material as waste according to section 13.
Pick up mechanically.
- Protective Action Criteria for Chemicals

· PAC-1:

CAS: 471-34-1	Calciumcarbonat	45 mg/m ³
CAS: 497-19-8	Soda leicht, Natriumcarbonat	7.6 mg/m ³
CAS: 554-13-2	Lithiumcarbonat	1.0 mg/m ³
CAS: 6381-59-5	Kalium-Natrium-Tartrat	12 mg/m ³
CAS: 144-55-8	Natriumhydrogencarbonat	13 mg/m ³
CAS: 10377-48-7	Lithiumsulfat	0.29 mg/m ³
CAS: 64742-52-5	Destillate (Erdöl), mit Wasserstoff behandelte schwere naphthenhaltige	140 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 3)

CAS: 7631-86-9	Kieselsäuren, amorphe	7.3 mg/m ³
· PAC-2:		
CAS: 471-34-1	Calciumcarbonat	210 mg/m ³
CAS: 497-19-8	Soda leicht, Natriumcarbonat	83 mg/m ³
CAS: 554-13-2	Lithiumcarbonat	11 mg/m ³
CAS: 6381-59-5	Kalium-Natrium-Tartrat	130 mg/m ³
CAS: 144-55-8	Natriumhydrogencarbonat	140 mg/m ³
CAS: 10377-48-7	Lithiumsulfat	3.2 mg/m ³
CAS: 64742-52-5	Destillate (Erdöl), mit Wasserstoff behandelte schwere naphthenhaltige	1500 mg/m ³
CAS: 7631-86-9	Kieselsäuren, amorphe	200 mg/m ³
· PAC-3:		
CAS: 471-34-1	Calciumcarbonat	1300 mg/m ³
CAS: 497-19-8	Soda leicht, Natriumcarbonat	500 mg/m ³
CAS: 554-13-2	Lithiumcarbonat	68 mg/m ³
CAS: 6381-59-5	Kalium-Natrium-Tartrat	790 mg/m ³
CAS: 144-55-8	Natriumhydrogencarbonat	840 mg/m ³
CAS: 10377-48-7	Lithiumsulfat	120 mg/m ³
CAS: 64742-52-5	Destillate (Erdöl), mit Wasserstoff behandelte schwere naphthenhaltige	8900 mg/m ³
CAS: 7631-86-9	Kieselsäuren, amorphe	1200 mg/m ³

- Reference to other sections hardened after contact with water
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- Precautions for safe handling Thorough dedusting.
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Avoid contact with skin and eyes.
Do not breathe dust.
Breathing apparatus only if aerosol or dust is formed.
protected above to humidity
- Information about protection against explosions and fires: Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: protected above to humidity in closing rooms
- Information about storage in one common storage facility: Not required
- Further information about storage conditions: Keep away from food and drink.
Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 4)

8 Exposure controls/personal protection

- Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS: 14808-60-7 Quarz (SiO₂)

PEL Long-term value: 0.05* mg/m³
*resp. dust; 30mg/m³/%SiO₂+2

REL Long-term value: 0.05* mg/m³
*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³
*respirable particulate matter, A2

CAS: 471-34-1 Calciumcarbonat

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV TLV withdrawn

CAS: 65997-15-1 Portland Cement

PEL Long-term value: 50 mppcf or 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 1* mg/m³
E; *as respirable fraction, A4

CAS: 10034-76-1 Calciumsulfat-Halbhydrat

TLV Long-term value: 10* mg/m³
*as inhalable fraction

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls
- Appropriate engineering controls No further data; see section 7.

- Personal protective equipment:

- General protective and hygienic measures:

Do not eat or drink while working.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.

- Breathing equipment:

Avoid contact with the eyes and skin.
Suitable respiratory protection for low concentrations or short-term exposure: particle filter EN 143 type P2 (medium retention capacity (solid and liquid pollutant particles))
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Breathing apparatus only if aerosol or dust is formed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 5)

- **Protection of hands:** **Protective gloves**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves** **Rubber gloves**
- **Penetration time of glove material** **The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.**
- **Eye protection:** **Tightly sealed goggles.**

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **Physical state** **Solid**
- **Color:** **Dark grey**
- **Odor:** **Characteristic**
- **Odor threshold:** **Not determined**
- **Melting point/Melting range:** **undetermined**
- **Boiling point/Boiling range:** **nicht anwendbar**
- **Flammability:** **Not determined**
- **Explosion limits:**
- **Lower:** **n. a. Vol %**
- **Upper:** **Not determined**
- **Flash point:** **Not applicable**
- **Auto igniting:** **n. a. °C**
- **Decomposition temperature:** **Not determined**
- **pH-value at 20 °C (68 °F):** **12 (5%)**
- **Viscosity:**
- **Kinematic:** **Not applicable**
- **Dynamic:** **Not applicable**
- **Solubility in / Miscibility with**
- **Water:** **is setting hydraulically**
- **Partition coefficient (n-octanol/water):** **Not determined**
- **Vapor pressure:** **Not applicable**
- **Vapor pressure:**
- **Density at 20 °C (68 °F):** **1.35 g/cm³ (11.26575 lbs/gal)**
- **Relative density** **Not determined**
- **Vapor density** **Not applicable**
- **Particle characteristics** **Not determined**
- **Other information** **The physical data are average values.**
- **Appearance:**
- **Form:** **Powder**
- **AUTO IGNITION:** **Not self igniting**
- **Danger of explosion:** **Product does not present an explosion hazard.**
- **Solvent content:**
- **VOC-Content** **0.00 %**
- **Solids content:** **100 %**
- **Change in condition**
- **Evaporation rate** **Not applicable.**

10 Stability and reactivity

- **Reactivity** **No further relevant information available.**

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 6)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *entrance of moisture
No decomposition if used and stored according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No decomposition if stored and applied as directed.*
- **Hazardous decomposition products:** *none under normal use*

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
- | | | |
|--|------|--------------------|
| CAS: 471-34-1 Calciumcarbonat | | |
| Oral | LD50 | >5,000 mg/kg (Rat) |
| CAS: 10034-76-1 Calciumsulfat-Halbhydrat | | |
| Oral | LD50 | >2,000 mg/kg (Rat) |
- **Primary irritant effect:**
- **on the skin:** *Irritant to skin and mucous membranes.*
- **on the eye:** *Strong irritant with the danger of severe eye injury.*
- **Sensitization:** *No sensitizing effects known.*
- **Experience with humans:** *The product contains cement. In combination with humidity the product provokes an alkaline reaction.
May cause eye/skin irritation.*
- **Additional toxicological information:** *According to concentration, aqueous solution causes irritations or burns of eyes, skin and mucous membranes.
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant*
- **Interactive effects** *No interactive effects between components are known.*
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
- | | | |
|----------------|-----------------------|---|
| CAS: 7631-86-9 | Kieselsäuren, amorphe | 3 |
| CAS: 128-37-0 | BHT | 3 |
- **NTP (National Toxicology Program)**
- | |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|
- **OSHA-Ca (Occupational Safety & Health Administration)**
- | |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|
- **Alternative sources for toxicological information** *No non-standard sources for toxicological information where used.*

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** *No further relevant information available.*
- **Persistence and degradability** *No further relevant information available.*
- **Bioaccumulative potential** *No further relevant information available.*

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 7)

- **Mobility in soil** *No further relevant information available.*
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable*
- **vPvB:** *Not applicable*
- **Other adverse effects**
- **Ecotoxicological effects:** *only by unintentional binding with much material and water is a highly pH-value possible*
- **Additional ecological information:**
- **General notes:** *Ecological injuries are not known or expected under normal use.
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.*

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** *Disposal in accordance with official regulations*
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

- | | |
|--|---|
| · UN-Number | |
| · DOT, ADR, ADN, IMDG, IATA | <i>Void</i> |
| · UN proper shipping name | |
| · DOT, ADR, ADN, IMDG, IATA | <i>Void</i> |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | <i>Void</i> |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | <i>Void</i> |
| · Environmental hazards: | |
| · Marine pollutant: | <i>No</i> |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | <i>Not applicable</i> |
| · Transport/Additional information: | <i>Not dangerous according to the above specifications.</i> |
| · Special precautions for user | <i>Not applicable</i> |

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 8)

· UN "Model Regulation": Void

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 554-13-2 Lithiumcarbonat

· TSCA (Toxic Substances Control Act):

CAS: 471-34-1	Calciumcarbonat	ACTIVE
---------------	-----------------	--------

CAS: 65997-16-2	Calcium Aluminate Cement	ACTIVE
-----------------	--------------------------	--------

CAS: 65997-15-1	Portland Cement	ACTIVE
-----------------	-----------------	--------

CAS: 497-19-8	Soda leicht, Natriumcarbonat	ACTIVE
---------------	------------------------------	--------

CAS: 554-13-2	Lithiumcarbonat	ACTIVE
---------------	-----------------	--------

	Hydroxyethylcellulose	ACTIVE
--	-----------------------	--------

CAS: 144-55-8	Natriumhydrogencarbonat	ACTIVE
---------------	-------------------------	--------

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

CAS: 14808-60-7 Quarz (SiO₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 554-13-2 Lithiumcarbonat

· New Jersey Right-to-Know List:

CAS: 65997-15-1 Portland Cement

CAS: 554-13-2 Lithiumcarbonat

CAS: 128-37-0 BHT

· New Jersey Special Hazardous Substance List:

CAS: 554-13-2	Lithiumcarbonat	TE
---------------	-----------------	----

· Pennsylvania Right-to-Know List:

CAS: 65997-15-1 Portland Cement

CAS: 7631-86-9 Kieselsäuren, amorphe

CAS: 128-37-0 BHT

· Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 9)

· TLV (Threshold Limit Value)

CAS: 128-37-0 BHT

A4

· MAK (German Maximum Workplace Concentration)

CAS: 128-37-0 BHT

4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS05 GHS08

· Signal word

Danger

· Hazard-determining components of labeling:

Quarz (SiO₂)

Portland Cement

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases. Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Chapters which have been revised from the previous issue are marked ***.

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his evaluation of the product's hazards, and safety precautions to be taken in its use. The data on this SDS relate only to the specific material

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 02/24/2026

Reviewed on 02/24/2026

Trade name: Servoplan Ki 1

(Contd. of page 10)

designated herein. We do not assume any liability for the use, or reliance in this information, nor do we guarantee its accuracy or completeness.

- **Department issuing SDS:** Health protection and safety
- **Date of previous version** 01/30/2026
- **Version number of previous version:** 56
- **Date of preparation** 02/24/2026
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - Skin irritation 2: Skin corrosion/irritation – Category 2
 - Eye damage 1: Serious eye damage/eye irritation – Category 1
 - Eye irritation 2A: Serious eye damage/eye irritation – Category 2A
 - Carcinogenicity 1A: Carcinogenicity – Category 1A
 - Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
- *** Data compared to the previous version altered.**

US