Okamul DF

Quick-drying, liquid applied elastomeric waterproofing and crack isolation membrane.

- flexible waterproofing for interior floors and walls, easy-to-apply, 2-coat system
- use for bathrooms, showers and other wet areas before the installation of tile, interior only
- extremely flexible
- excellent crack isolation characteristics
- very quick drying, no odour
- apply with roller brush or trowel – easy to install over avariety of approved substrates
- bonds to a wide range of surfaces; convenient, user-friendly and versatile
- prevents in-plane floor cracks from transmitting through tile or stone
- crack isolation up to $^{1}/_{8}$" (3 mm)
- highly stable consistency; minimized drips and splatters
- can be brushed, rolled or trowelled

Kiesel

APPLICATION

The substrate must be dry, clean, sound and suitable for the given water exposure class. Prime absorbent substrates with Okatmos® DSG or Okatmos® UG 30. To avoid cracking in corners and on vertical and horizontal planes, use Kiesel self-adhering tape.

Note: Any necessary leveling or rapair work on porous substrates must be carried out beforehand.

After the 1st coat has dried to the touch (within 1 hr), a 2nd coat must be applied. The minimum wet film thickness for two coats is 0.7 mm. Minimum dry film thickness 0.5 mm. Checking the required wet film thickness must be ensured via consumption or a measuring comb. Wait approximately 4 hours before walking or tiling.

Technical properties

Packaging/palletizing	Item no.
40 x 2.47 U.S. gals./14 kg rectangular plastic bucket	12010 light grey
60 x 1.23 U.S. gals./7 kg oval plastic bucket	12014 light grey

The detailed technical data sheet for the product can be found at **ca.kiesel.com** or **us.kiesel.com**

WE ARE HERE FOR YOU:

CA.KIESEL.COM

US.KIESEL.COM

Kiesel Bauchemie GmbH u. Co. KG
Wolf-Hirth-Strasse 2
73730 Esslingen, Germany
Tel. +49 711 93134-0
Fax +49 711 93134-140
kiesel@kiesel.com

Technical Department of North America
Toll-Free: 1.888.KIESEL1 (5437351)
info.canada@kiesel.com
info.usa@kiesel.com

Kiesel klebt am Bau®

Key to quality installation

Stand: 05/2024