CHANGE THE WAY YOUR WORK WITH KIESEL BRAND THINSETS

- **Engineered to save time and perform like nothing else in the US market.**
- **From installing small mosaic to thin gauge porcelain slab, we have you covered.**
- **All Kiesel thinsets are made in Germany with the highest-grade raw materials and the newest technologies available.**
- **Kiesel thinsets are self-curing, S1 & S2 rated and set the industry standard for non-sag.**
- **The abundant transfer from our wet mixtures allows you to achieve better coverage with less effort.**
- **The price per square foot is comparable to less expensive thinsets due to the extended coverage because of light weight fillers used in our formular; our 27.5 lb bag covers the same as a 50 lb bag.**
- **If green is what you are looking for, look no further than Kiesel with our EMICODE EC1 Plus rated, 0,0 g/L VOC and approximately 25% post-consumer recycled products with dust reduced technology*.**
- **Our thinsets are freeze-thaw stable, sutiable for interior/exterior and submerged applications*.**

	Ready to grout in (hour)	Mortar flexability (mm)	Interior	Exterior	Submeersible	Floor	Wall	Ceiling	Large format	Slab	Thin GA slab
Servolight	12	2.5-5	✔	✔	✔	✔	❤	❤	❤	✔	Interior Walls*
Servolight S2	12	≥ 5	❤	❤	❤	❤	❤	❤	❤	❤	Interior Floors*✓ Exterior Walls* Exterior Floors*
Servoflex Trio	12	2.5-5	✔	✔		❤			❤	❤	
Servoflex 5	**4-6**	2.5-5	❤	❤	❤	❤	✔		✔	✔	Interior Walls*
Servoflex Pro	12	2.5-5	❤	❤	❤	❤	✔		✔		Interior Walls*

WWW.US.KIESEL.COM
1-800-KIESEL1

WWW.CA.KIESEL.COM
1-800-KIESEL1

This flyer serves as general information and should only be used as such. For more relevant details, application processes, suitability and environmental info before commencing installation work, please visit our North American websites.

Kiesel

Servolight
Premium extended coverage flexible thin set mortar

- one component, no additives required
- up to twice the coverage of a standard thin-set mortar
- easy to trowel with extended open time, light grey
- non-sag formula for large-and-heavy coverings and porcelain slabs (GPTP)
- excellent for wall and floor tile installations
- freeze / thaw stable, self curing
- interior, exterior and submergible applications

Coverage:
1/2" x 1/2" x 1/2" sq notched trowel approx. 50 sq ft per bag

A 118.4
C2 TE-S1

72 x 27.5 lbs
Item no. 80010

9/16"

Servolight S2 SuperTec
Premium extremely flexible extended coverage thin set mortar

- one component, no additives required
- up to twice the coverage of a standard thin-set mortar
- easy to trowel with extended open time, light grey
- non-sag formula for large-and-heavy coverings and porcelain slabs (GPTP)
- excellent for wall and floor tile installations
- freeze / thaw stable, self curing
- interior, exterior and submergible applications

Coverage:
1/2" x 1/2" x 1/2" sq notched trowel approx. per 58 sq ft per bag

A 118.4
C2 TE-S2

54 x 33 lbs
Item no. 80081

200 x 6.6 lbs
Item no. 13103

9/16"

Servoflex-Trio-SuperTec
Premium flexible full transfer thin set and medium bed mortar

- thinset and medium bed mortar up to 3/4" thickness
- one component, no additives required
- up to twice the coverage of a standard thin-set mortar
- easy to trowel with extended open time, light grey
- non-sag formula for large-and-heavy floor tiles
- full mortar transfer, no billowing of mortar through joints
- can also be used over heated screeds, balconies and patios
- freeze / thaw stable, self curing
- interior, exterior and submergible applications

Coverage:
1/2" x 1/2" x 1/2" sq notched trowel approx. 65 sq ft per bag

A 118.4
C2 E-S1

54 x 44 lbs
White item no. : 80022
Grey item no. 80024

3/4"

Servoflex 5 royal SuperTec
Premium thinset, medium bed and leveling/repair mortar with an accelerated curing

- thinset and medium bed mortar up to 3/4" thickness.
- for walls and floors installations.
- for interior, exterior and submergible applications, excellent for uncoupling membranes.
- efflorescence free, aluminate cement based with acrylic polymers.
- fully cured after 12 hours for commercial traffic*.
- fully walkable and ready to grout after 4 hours over absorbent substrates and under and over uncoupling membranes after 6 hours*
- can be exposed to rain after 4–6 hours*
- post-consumer recycled content -25%
- extended coverage approximately 30%
- non-sag exceeding industry requirements
- excellent adhesion and accelerated drying/curing times over/under uncoupling membranes

Coverage:
1/2" x 1/2" x 1/2" sq notched trowel approx. 50 ft. per bag

A 118.15 LHT
(pending)
C2 FTE-S1

72 x 27.5 lbs
Item no. 13155

13/16"

Servoflex Pro
The contractor's preferred mortar

- use of mineral co-binders instead of artificial ones
- conservation of natural resources
- cement-reduced formulation, less CO2 emissions
- variable, adjustable water factor for walls and floors
- safe and rapid hardening even under XL tiles
- extended coverage indoors and outdoors, on walls and floors, submergible

Coverage:
1/2" x 1/2" x 1/2" (12 mm) 37 ft^2. per bag

C2 TE-S1

72 x 27.5 lbs
Item no. 80361

5/8"

*Coverage is approximate and is given for estimating purposes only. It may vary according to substrate conditions and other factors. At 68 °F (+20 °C) and 65 % relative humidity. Higher temperatures and low humidity decrease, lower temperatures and high humidity increase this value respectively. Avoid air entrapment doing exterior and underwater installations. Apply mortar on the substrate and backside of tiles (back-buttering procedure). Lift tiles and check for proper mortar transfer. Always check the latest technical data sheet.